



BERKSHIRE

A modern and stylish IP55 rated stainless steel LED Bollard.

APPLICATIONS

Parks and gardens & urban amenity areas

SPECIFICATION

Aluminium louvres for optimum performance & minimal upward light

LED rating 1701lm

-20 to +40°C operating temperature

Osram LED & Osram Driver

Removable head for easy access to LED & Driver

Surface mount bracket available

Options available include bolt-on root, 180° spill shield & 3hr emergency.

CONSTRUCTION

304 stainless steel with strong UV stabilised polycarbonate lens & tamper proof fixings

DIMENSIONS Ø180 x H960mm



CLASS 1 	WEIGHT 7Kg
LED 	LIFE 100000 hrs Lamp Life
VANDAL PROOF IK10	WATER & DUST IP55

BEI CODE	DESCRIPTION
BER20-6K-SS304	20W Cool White 6000K
BER20-4K-SS304	20W Neutral White 4000K

MALVERN

A classic IP55 rated Black Flat Head LED bollard, creating an energy efficient and attractive outdoor feature.

APPLICATIONS

Parks and gardens & urban amenity areas

SPECIFICATION

Aluminium louvres for optimum performance & minimal upward light

LED rating 2400lm

-20 to +40°C operating temperature

Osram LED & Osram Driver

Removable head for easy access to LED & Driver

Options available include bolt-on root, 180° spill shield, mini photocell & 3hr emergency

CONSTRUCTION

Die cast aluminium with strong UV stabilised polycarbonate lens & tamper proof fixings

DIMENSIONS Ø180 x H980mm



CLASS 1 	WEIGHT 7Kg
LED 	LIFE 100000 hrs Lamp Life
VANDAL PROOF IK10	WATER & DUST IP55

BEI CODE	DESCRIPTION
MAL20-6K-STD	20W Cool White 6000K
MAL20-4K-STD	20W Neutral White 4000K

CHILTON

A classic IP55 rated Black Dome Head LED bollard creating, an energy efficient and stylish outdoor feature.

APPLICATIONS

Parks and gardens & urban amenity areas

SPECIFICATION

White coated steel Louvres for optimum performance & minimal upward light

LED rating 1642lm

-20 to +40°C operating temperature

LED Life span > 100,000hrs

Osram LED & Osram Driver

Removable head for easy access to LED & Driver

Options available include bolt-on root, 180° Spill Shield, Mini Photocell & 3hr Emergency

CONSTRUCTION

Die cast aluminium with strong UV stabilised polycarbonate lens & tamper proof fixings

DIMENSIONS Ø180 x H1000mm



CLASS 1 	WEIGHT 7Kg
LED 	LIFE 100000 hrs Lamp Life
VANDAL PROOF IK10	WATER & DUST IP55

BEI CODE	DESCRIPTION
NEL20-6K-STD	20W Cool White 6000K
NEL20-4K-STD	20W Neutral White 4000K

COTSWOLD

A beautifully designed wooden bollard with a 120° beam LED, making an impressive addition to any project.

APPLICATIONS

Parks and gardens & urban amenity areas

SPECIFICATION

Contains LED lamp that can be changed at end of life

LED rating 400lm

-20 to +40°C operating temperature

Surface mount bracket available

CONSTRUCTION

Iroko wood with cleverly designed cut angles

DIMENSIONS Ø94 x H1100mm



CLASS 1 	WEIGHT 4Kg
LED 	LIFE 25000 hrs Lamp Life
VANDAL PROOF IK10	WATER & DUST IP55

BEI CODE	DESCRIPTION
COT5-6K-STD	5W Cool White 6000K
COT5-3K-STD	5W Warm White 3000K